

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
11 April 2002 (11.04.2002)

PCT

(10) International Publication Number  
WO 02/29229 A1(51) International Patent Classification<sup>7</sup>: F02D 41/14,  
33/02, F02B 37/22(72) Inventor; and  
(75) Inventor/Applicant (for US only): SHIRAKAWA,  
Takashi [JP/JP]; 2-92, Urage-cho, Yokosuka-shi, Kana-  
gawa 237-0062 (JP).

(21) International Application Number: PCT/JP01/07694

(22) International Filing Date:  
5 September 2001 (05.09.2001)(74) Agent: GOTO, Masaki; Shoyu-Kaikan, 3-1, Kasumi-  
gaseki 3-chome, Chiyoda-ku, Tokyo 100-0013 (JP).

(25) Filing Language: English

(81) Designated States (national): CN, KR, US.

(26) Publication Language: English


(84) Designated States (regional): European patent (AT, BE,  
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,  
NL, PT, SE).(30) Priority Data:  
2000-306484 5 October 2000 (05.10.2000) JP

Published:

— with international search report  
— before the expiration of the time limit for amending the  
claims and to be republished in the event of receipt of  
amendments(71) Applicant (for all designated States except US): NISSAN  
MOTOR CO., LTD. [JP/JP]; 2, Takara-cho, Kana-  
gawa-ku, Yokohama-shi, Kanagawa 221-0023 (JP).

[Continued on next page]

(54) Title: CONTROL OF SUPERCHARGER



(57) Abstract: The intake air amount of an engine (1) is controlled by a variable nozzle (53) of a turbocharger (50). A controller (41) calculates an open loop control value of a drive signal of the variable nozzle (53) based on a running state of the engine (1), and calculates a feedback correction amount comprising an integral correction value of the drive signal such that the intake air amount coincides with a target intake fresh air amount (S367). It also calculates a learning value based on the integral correction value when the intake air amount coincides with the target intake air amount (S395, S400), and modifies the feedback correction amount such that the sum of the learning value and feedback correction amount is constant (S366). In this way, the response of intake air amount control or supercharging pressure control is enhanced.



WO 02/29229 A1